



Panel (PLP) compatible small reflow oven

UNI-6146

The UNI-6146 is a compact reflow oven compatible with panel-level packages (PLPs) with a transport width of 460mm. Despite its compact design of less than 2m in length, its 6-zone heating and cooling structure enables profile reproduction equivalent to that of mass-production reflow lines. It can handle low-oxygen environments and high-temperature processes up to 400° C, and is suitable for a wide range of applications, from PLPs (panel-level packages) to bump formation, prototyping and development, and thermal evaluation.

Standard specifications

Number of zones	6 heating zones / 1 cooling zone	Flux recovery mechanism	Option
Heating method	Top hot air + far-infrared heating	PC outlet	1 piece (100V)
	Lower hot air + far-infrared heating	Pass line	900 ± 20mm
Maximum set temperature	Top 350°C / Bottom 350°C	Input power (*2)	AC200V 3 φ 23kVA 67A
Board effective width	50~460mm	Stable power consumption	Approximately 6kW/h
Conveying method	Pin chain / Mesh	Device dimensions	L1,990 × D1,320 × H1,410mm
Conveying speed	0.1~0.5m/min	Equipment weight	850kg
Part effective height(*1)	Top surface 10mm / Bottom surface 10mm	*1: Adjustable via the labyrinth up/down mechanism.	
Oxygenconcentration meter	Standard equipment	*2: Input power is used in peak power suppression mode.	

Option

① Automatic width adjustment mechanism	⑨ Oxygen concentration sampling across all zones
② Overheating Prevention Device	⑩ Low oxygen concentration specification (100 ppm or less)
③ Board drop sensor	⑪ Labyrinth Up/Down Mechanism
④ Simple maintenance type flux recovery mechanism	⑫ Entrance/exit conveyor extension
⑤ UPS (Uninterruptible Power Supply)	⑬ Circulation fan stop detection
⑥ High temperature compatible (maximum setting temperature 400°C)	⑭ Hood interlock
⑦ Oxygen concentration controller	⑮ Reflow checker (profile measurement unit)
⑧ N2 All Zones Supply	⑯ Various conveyors (conveyor, cooling conveyor, loader, unloader)

*Regarding safety specifications and compliance with various standards, we can provide individual support according to your requirements.

Contact information

Antom Co., Ltd.

893-1 Kawamukai-cho, Tsuzuki-ku, Yokohama City, Kanagawa Prefecture 224-0044

TEL: +81-45-476-3461 (Weekdays 8:30 AM - 5:30 PM) WEB : <https://antom.co.jp/en>

QR code for website



*The copyright for the contents of this catalog belongs to Antom Co., Ltd. Unauthorized reproduction, copying, or modification is prohibited.

*The specifications and appearance of the product may change without notice due to product improvements.