



Medium-sized reflow oven (N2 compatible)

EXSOL-6136

Standard specifications

Number of zones	6 heating zones / 1 cooling zone
Heating method	Upper hot air + far infrared heating Lower far infrared heating
Maximum set temperature	Upper 320°C / Lower 350°C
Effective width for workpiece transport	50 ~ 360 mm
Transport method	Pin chain / mesh
Conveying speed	0.3 ~ 1.5 m/min
Part effective height	Top 10 mm / Bottom 10 mm
Supported languages	Japanese, English, Chinese, Korean
Flux Recovery Mechanism	Easy maintenance flux recovery
Board mounting fee	4 mm
Pass line	900 ± 20 mm
Input power	Pass line AC 200 V 3 φ 37 kVA 107 A
Stable power consumption	Approximately 7 kW/h
Equipment dimensions	L2,995 × D1,300 × H1,305mm
Equipment weight	1,300 kg

Option

Automatic width adjustment mechanism
Overheat prevention mechanism
Board drop sensor
Lifting type anti-sliding mechanism
UPS (uninterruptible power supply)
Oxygen concentration controller
N2 All Zone Supply
Oxygen concentration full zone sampling
Labyrinth up/down mechanism
Low oxygen concentration specification (100 ppm or less)
Entrance/exit conveyor extension
Circulation fan stop detection sensor
Hood interlock
Various conveyors (loaders, unloaders, etc.)
Customization available (consultation required)

893-1 Kawamukae-cho, Tsuzuki-ku, Yokohama,
Kanagawa Prefecture, 224-0044
TEL: +81-45-476-3461
(Person in charge: Suzuki or Yada)
Email: eigyou@antom.co.jp
URL: <https://antom.co.jp/>

